




LED HIGH BAY LIGHT

- Available in 7 wattages: 100W, 150W, 200W, 240W, 300W, 400W, 500W
- Hook with screw, 5' cord for input and dimming wires
- Die-cast aluminum heatsink anti-corrosion housing
- Ribbed lens to reduce glare
- 0~10V dimming SOSEN LED driver
- 50,000hrs lifespan, 5 years warranty
- IP65 rated, wet location
- ETL, CE, DLC premium rated



*Optional

- 100-277/ 277-480VAC input voltage.
- Emergency battery backup
- 60°/ 90°/ 120° Beam angle.
- PC & Aluminum reflector.
- Microwave sensor kits.
- CCT & Watt tunable.
- US Plug



Emergency battery backup



Microwave Remote Control



Microwave Sensor


Applications

LED UFO high bay are ideal for replacing HID/ HPS/ MHL high bay fixtures.


Applications such as warehouses workshop and manufacturing facilities and industrial buildings any indoor or outdoor commercial and industrial area.



Workshop



Basketball hall




Fitness Room



Storehouse


100W

Weight: 1500g/ 3.31 lbs




150W

Weight: 1700g/ 3.75 lbs




200W

Weight: 2000g/ 4.41 lbs




240W

Weight: 2500g/ 5.51 lbs




300W

Weight: 3800g/ 8.38 lbs




400W/ 500W

Weight: 6500g/ 14.33 lbs




Series	Lumens	LED Type	Beam Angle (Degree)	Electrical Data	Color Temperature	Color Rendering Index
NG-UFO-100W	15000 Lm	240 PCS (120PCS - 4500K) (120PCS - 5700K)	90°/ 120°	Input Voltage 100-277VAC or AC277-480V 50~60Hz Power Factor(>)>90	WW: 3000K NW: 4000K DW: 5000K CW: 5700K	Ra≥80
NG-UFO-150W	22500 Lm	320 PCS (160PCS - 4500K) (160PCS - 5700K)				
NG-UFO-200W	30000 Lm	480 PCS (240PCS - 4500K) (240PCS - 5700K)				
NG-UFO-240W	36000 Lm	640 PCS (320PCS - 4500K) (320PCS - 5700K)	60° /90°/ 120°	Input Voltage 100-277VAC 50~60Hz Power Factor(>)>90		
NG-UFO-300W	45000 Lm	640 PCS (320PCS - 4500K) (320PCS - 5700K)				
NG-UFO-400W	60000 Lm	800 PCS SMD 2835 Chips				
NG-UFO-500W	75000 Lm	800 PCS SMD 2835 Chips				


1. Open the box and take out the LED light and ring.
2. Install the ring into the light body as following diagram.



3. Hung the LED light with a sturdy hook.



4. Hang the safety wire one side to the lamp, another side to the sturdy hook shown by diagram.




5. Connect wires as below diagram and turn on power to lighting.

Black wire : L


Green wire: 

White wire : N


UL: (White:N)
(Green GND)
(Black:L)




6. 0-10V DIM only valid for dimmable function (DIM+ DIM-), Pls ignore if no need dimmable or for Non-dimmable Model.




1:



2:



3:



1. UNSCREW THE CAP. 2. ADJUST PROPERLY POWER OR CCT. 3. SCREW THE CAP.

CCT Selections:

There are 3 color temperatures available (CW/NW/WW)
Please select the color temperature you prefer before installation


CW	NW	WW
5700K	5000K	4500K

Power Selections:

There are 3 power options (A/B/C), please select the power according to your needs

UFO100W	A	B	C
	100W	80W	60W
UFO200W	A	B	C
	200W	160W	120W
UFO300W	A	B	C
	300W	240W	180W
UFO500W	A	B	C
	500W	400W	300W

UFO150W	A	B	C
	150W	120W	90W
UFO240W	A	B	C
	240W	200W	150W
UFO400W	A	B	C
	400W	320W	240W



Power	Unit	Size	Gross Weight	Volume
NG-UFO-100W	10 PCS	535x500x435mm/ 21.06**19.68**17.12"	19.5 KG/ 42.99 lbs	0.116m ³
NG-UFO-150W	6 PCS	580x300x585mm/ 22.83**11.81**23.03"	14 KG/ 30.86 lbs	0.102m ³
NG-UFO-200W	4 PCS	535x335x515mm/ 21.06**13.19**20.27"	11.5 KG/ 25.35 lbs	0.092m ³
NG-UFO-240W	3 PCS	540x375x380mm/ 21.26**14.76**14.96"	11 KG/ 24.25 lbs	0.077m ³
NG-UFO-300W	3 PCS	570x385x390mm/ 22.44**15.16**15.35"	13.8 KG/ 30.42 lbs	0.086m ³
NG-UFO-400W NG-UFO-500W	2 PCS	475x420x485mm/ 18.7**16.54**19.09"	14.8 KG/ 32.63 lbs	0.097m ³