

Product Descriptions

INTENDED Purchase - The LED Corn bulbs is light for replace traditional 360 degree lights such as metal halide,CFL,HID, HPS for parking lot,gas station,warehouse indoor and outdoor energy saving purpose.Design install into existing fixture with cost-effective solution.

STRUCTURE -Fin heatsink sunon fan active cooling solution,PC cover protect LEDs from dust,insect and humidity working environment.Driver fully sealed by thermal paste with function to disperse heat into outside Adopt 150LM/W LED chips improve light efficiency.

OPTICS - Milky and Transparent PC cover for choice range from 30W~ 300W with E26,E27, E39,E40 socket for choice in different application sealed or open fixture.

ELECTRICAL - Standard 6kV surge protection,regular input voltage 100~ 277V,no ballast need.

INSTALLATION - Easily fitted in traditional fixture instead of MHL and HPS.

LISTINGS - CE,UL,cUL, ETL certification approved.
Suitable for sealed,dry,humidity working environment from -40°C up to 45°C.

WARRANTY - 5 years warranty.
Replaceable driver part design.Free provide materials replacement easy for customer replace.
We will responsible if damaged or quality problem.
like damaged under shipment. Screws loosen.Driver problem.

NOTICE:

160W~300W LED Corn bulbs not allowed install in enclosed fixture due to overheat.
Only suitable for indoor open fixture.

Features

- E39 E40 Mogul screw base
- CE, UL, CUL, ETL approved
- 100~277V, 480V, 347V high voltage input
- Sunon Fan active cooling
- 360° Degree Beam Angle
- Aluminum fin heat sink
- PC Cover milky&clear
- 6K High voltage surge test approved
- SMD2835 150lm/w led chips
- 50,000hrs lifespan
- Top Brand Rubycon Capacitor
- OEM special design company logo
- No UV or IR radiation
- No magnetic disturbance driver design
- Replace 100~1000W metal halide/HPS
- Application in warehouse, parking lot, street, gas station etc..



30W

60W



80W

100W

120W



160W

200W

250W

300W


LED CORN LIGHT

Series	Lumens	Base	Beam Angle (Degree)	Electrical Data	LED Type	Color Temperature	Color Rendering Index	Ambient Temperature	Material
NGWL-30W12S	4500Lm	E26 E27 E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	220PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NGWL-60W12S	9000Lm	E26 E27 E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	490PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-80W14S	12000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	610PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-100W14S	15000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	644PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-120W14S	18000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	840PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-160W16S	24000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	1232PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-200W16S	30000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	1232PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-250W16S	37500Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	1652PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-300W16S	45000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC100-277V 50~60Hz Power Factor(%) >90	1919PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum


LED CORN LIGHT

Series	Lumens	Base	Beam Angle (Degree)	Electrical Data	LED Type	Color Temperature	Color Rendering Index	Ambient Temperature	Material
NG-WL-60WH	9000Lm	E26 E27 E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	490PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-80WH	12000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	610PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-100WH	15000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	644PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-120WH	18000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	840PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-160WH	24000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	1232PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-200WH	30000Lm	E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	1232PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum
NG-WL-250WH	37500Lm	E39 E40	360 degree Beam Angle	Input Voltage AC277-480V 50~60Hz Power Factor(%) >90	1652PCS SMD 2835 Chips	WW 2800~3200 K NW 4000~4500 K DW 5000~5500 K CW 6000~6500 K	Ra>80	-40~45 C	PBT+Aluminum


DIMENSION



Series	Φ	W	M	L	H
NGWL-30W12S	2.716" (69MM)	3.54" (90MM)	1.77" (45MM)	2.87" (73MM)	7.145" (181.5MM)
NGWL-60W12S	2.716" (69MM)	3.54" (90MM)	1.77" (45MM)	2.87" (73MM)	9.37" (238MM)
NG-WL-60WH	2.716" (69MM)	3.54" (90MM)	1.77" (45MM)	2.87" (73MM)	9.37" (238MM)




Series	Φ	W	M	L	H
NG-WL-80W14S	3.937" (100MM)	4.8" (122MM)	1.77" (45MM)	3.15" (80MM)	9.96" (253MM)
NG-WL-100W14S	3.937" (100MM)	4.8" (122MM)	1.77" (45MM)	3.15" (80MM)	10.75" (273MM)
NG-WL-120W14S	3.937" (100MM)	4.8" (122MM)	1.77" (45MM)	3.15" (80MM)	11.93" (303MM)
NG-WL-80WH	3.937" (100MM)	4.8" (122MM)	1.77" (45MM)	3.15" (80MM)	9.96" (253MM)
NG-WL-100WH	3.937" (100MM)	4.8" (122MM)	1.77" (45MM)	3.15" (80MM)	10.75" (273MM)
NG-WL-120WH	3.937" (100MM)	4.8" (122MM)	1.77" (45MM)	3.15" (80MM)	11.93" (303MM)



Series	Φ	W	M	L	H
NG-WL-160W16S	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	12.01" (305MM)
NG-WL-200W16S	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	13.19" (335MM)
NG-WL-250W16S	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	13.19" (335MM)
NG-WL-300W16S	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	14.37" (365MM)
NG-WL-160WH	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	12.01" (305MM)
NG-WL-200WH	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	13.19" (335MM)
NG-WL-250WH	4.4" (112MM)	5.24" (133MM)	1.77" (45MM)	3.15" (80MM)	13.19" (335MM)

NGWL-30W



Chroma Parameters
Chro.Coor.:x=0.3706 y=0.3775 u=0.2184 v=0.3336 duv=0.0033
CCT: 4282K Dominant Wave.:576.0nm Purity:24.5%
Flux RGB Ratio:R=15.8%,G=82.6%,B=1.6% Peak Wave:445.6nm Half Width:18.6nm


Rendering Index:Ra= 71.2
R1 =69 R2 =76 R3 =82 R4 =72 R5 =69 R6 =67 R7 =81 R8 =55
R9 =0 R10=43 R11=69 R12=40 R13=69 R14=90 R15=62

Photo Parameters
Flux:4056.09lm Effi.:130.2lm/W Radiant:9355.0mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.500V Current:I=0.1560A
Power:P=33.27W Power Factor:PF=0.967

Instrument state
Instrument:Hopoo HP8000S Integral Time: 5.520ms VPeak: 11024
VDark: 1239 Scan Range: 380-780nm Product ID: 201308416

NGWL-60W



Chroma Parameters
Chro.Coor.:x=0.3709 y=0.3796 u=0.2178 v=0.3343 duv=0.0042
CCT: 4287K Dominant Wave.:575.5nm Purity:25.2%
Flux RGB Ratio:R=15.7%,G=82.7%,B=1.7% Peak Wave:445.6nm Half Width:17.5nm


Rendering Index:Ra= 71.4
R1 =69 R2 =76 R3 =83 R4 =72 R5 =68 R6 =67 R7 =81 R8 =55
R9 =0 R10=44 R11=69 R12=39 R13=69 R14=90 R15=62

Photo Parameters
Flux:8210lm Effi.:134.6lm/W Radiant:20906.2mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.400V Current:I=0.2800A
Power:P=60.50W Power Factor:PF=0.980

Instrument state
Instrument:Hopoo HP8000S Integral Time: 1.185ms VPeak: 6066
VDark: 1255 Scan Range: 380-780nm Product ID: 201308416

NG-WL-80W



Chroma Parameters
Chro.Coor.:x=0.3200 y=0.3377 u=0.1996 v=0.3160 duv=0.0040
CCT: 6082K Dominant Wave.:496.0nm Purity:4.2%
Flux RGB Ratio:R=12.5%,G=85.2%,B=2.3% Peak Wave:443.5nm Half Width:18.9nm


Rendering Index:Ra= 71.2
R1 =70 R2 =73 R3 =76 R4 =73 R5 =72 R6 =67 R7 =78 R8 =60
R9 =0 R10=38 R11=74 R12=47 R13=69 R14=87 R15=64

Photo Parameters
Flux:11092.89lm Effi.:124.8lm/W Radiant:31003.4mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.400V Current:I=0.4180A
Power:P=88.87W Power Factor:PF=0.962

Instrument state
Instrument:Hopoo HP8000S Integral Time: 1.524ms VPeak: 13384
VDark: 1234 Scan Range: 380-780nm Product ID: 201308416

NG-WL-100W



Chroma Parameters
Chro.Coor.:x=0.3719 y=0.3787 u=0.2188 v=0.3341 duv=0.0035
CCT: 4251K Dominant Wave.:576.1nm Purity:25.3%
Flux RGB Ratio:R=15.7%,G=82.7%,B=1.6% Peak Wave:445.6nm Half Width:18.9nm


Rendering Index:Ra= 70.3
R1 =66 R2 =74 R3 =81 R4 =73 R5 =69 R6 =68 R7 =80 R8 =52
R9 =0 R10=40 R11=69 R12=40 R13=66 R14=89 R15=59

Photo Parameters
Flux:13442.61lm Effi.:131.0lm/W Radiant:34149.4mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.400V Current:I=0.4780A
Power:P=102.60W Power Factor:PF=0.972

Instrument state
Instrument:Hopoo HP8000S Integral Time: 2.072ms VPeak: 14944
VDark: 1212 Scan Range: 380-780nm Product ID: 201308416

NG-WL-120W



Chroma Parameters
Chro.Coord.:x=0.3201 y=0.3384 u=0.1994 v=0.3162 duv=0.0043
CCT: 6075K Dominant Wave.:496.7nm Purity:4.2%
Flux RGB Ratio:R=12.5%,G=85.2%,B=2.4% Peak Wave:443.5nm Half Width:19.1nm


Rendering Index:Ra= 71.0
R1 =70 R2 =73 R3 =77 R4 =73 R5 =72 R6 =66 R7 =78 R8 =59
R9 =0 R10=38 R11=74 R12=47 R13=69 R14=87 R15=63

Photo Parameters
Flux:15317.67lm Effi.:129.4lm/W Radiant:43429.0mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.300V Current:I=0.5490A
Power:P=118.40W Power Factor:PF=0.979

Instrument state
Instrument:Hopoo HP8000S Integral Time: 1.237ms VPeak: 15130
VDark: 1236 Scan Range: 380-780nm Product ID: 201308416

NG-WL-160W



Chroma Parameters
Chro.Coord.:x=0.3198 y=0.3373 u=0.1996 v=0.3158 duv=0.0039
CCT: 6096K Dominant Wave.:495.5nm Purity:4.3%
Flux RGB Ratio:R=12.5%,G=85.2%,B=2.3% Peak Wave:443.5nm Half Width:19.4nm


Rendering Index:Ra= 71.2
R1 =70 R2 =73 R3 =76 R4 =73 R5 =72 R6 =67 R7 =78 R8 =60
R9 =0 R10=37 R11=74 R12=47 R13=69 R14=87 R15=64

Photo Parameters
Flux:21858.60lm Effi.:134.5lm/W Radiant:53253.8mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.300V Current:I=0.7450A
Power:P=164.20W Power Factor:PF=0.977

Instrument state
Instrument:Hopoo HP8000S Integral Time: 1.000ms VPeak: 14672
VDark: 1245 Scan Range: 380-780nm Product ID: 201308416

NG-WL-200W



Chroma Parameters
Chro.Coord.:x=0.3198 y=0.3373 u=0.1996 v=0.3158 duv=0.0039
CCT: 6096K Dominant Wave.:495.5nm Purity:4.3%
Flux RGB Ratio:R=12.5%,G=85.2%,B=2.3% Peak Wave:443.5nm Half Width:19.4nm


Rendering Index:Ra= 71.2
R1 =70 R2 =73 R3 =76 R4 =73 R5 =72 R6 =67 R7 =78 R8 =60
R9 =0 R10=37 R11=74 R12=47 R13=69 R14=87 R15=64

Photo Parameters
Flux:25625.80lm Effi.:125.5lm/W Radiant:53253.8mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.300V Current:I=0.9530A
Power:P=205.20W Power Factor:PF=0.977

Instrument state
Instrument:Hopoo HP8000S Integral Time: 1.000ms VPeak: 14672
VDark: 1245 Scan Range: 380-780nm Product ID: 201308416

NG-WL-250W



Chroma Parameters
Chro.Coord.:x=0.3198 y=0.3373 u=0.1996 v=0.3158 duv=0.0039
CCT: 6096K Dominant Wave.:495.5nm Purity:4.3%
Flux RGB Ratio:R=12.5%,G=85.2%,B=2.3% Peak Wave:443.5nm Half Width:19.4nm


Rendering Index:Ra= 71.2
R1 =70 R2 =73 R3 =76 R4 =73 R5 =72 R6 =67 R7 =78 R8 =60
R9 =0 R10=37 R11=74 R12=47 R13=69 R14=87 R15=64

Photo Parameters
Flux:33540.20lm Effi.:130.6lm/W Radiant:53253.8mW Ri:0.0mW/sr

Ele. Parameters
Voltage:U=220.300V Current:I=0.9530A
Power:P=258.20W Power Factor:PF=0.977

Instrument state
Instrument:Hopoo HP8000S Integral Time: 1.000ms VPeak: 14672
VDark: 1245 Scan Range: 380-780nm Product ID: 201308416

NG-WL-300W



Chroma Parameters

Chro.Coor.:x=0.3198 y=0.3373 u=0.1996 v=0.3158 duv=0.0039
CCT: 6096K Dominant Wave.:495.5nm Purity:4.3%
Flux RGB Ratio:R=12.5%,G=85.2%,B=2.3% Peak Wave:443.5nm Half Width:19.4nm

Rendering Index:Ra= 71.2

R1 =70 R2 =73 R3 =76 R4 =73 R5 =72 R6 =67 R7 =78 R8 =60
R9 =0 R10=37 R11=74 R12=47 R13=69 R14=87 R15=64

Photo Parameters

Flux:39280.50lm Effi.:130.6lm/W Radiant:53253.8mW Ri:0.0mW/sr

Ele. Parameters


Voltage:U=220.300V Current:I=0.9530A
Power:P=300.20W Power Factor:PF=0.977

Instrument state



Instrument:Hopoo HP8000S Integral Time: 1.000ms VPeak: 14672
VDark: 1245 Scan Range: 380-780nm Product ID: 201308416

SCHEMATIC DIAGRAM

REPLACE CFL



REPLACE HPS



INSTALLATION

1.Remove old ballast or disconnect from existing lamp holder.

Remove and dispose of ballast in correct manner.

Shown as Figure 1.(North America 100-277 VAC)

Fig 1




Fig 2

2.Reconnect directly to the existing lamp holder. Shown as Figure 2

(North America 100-277VAC)





Fig 3

3.Install New LED Replacement lamp. Shown as Figure 3. Please make sure the old fitting is correctly earth. (North America 100-277VAC)



APPLICATION

Flood Light Fixture



Cobra Fixture



Post Top Fixture



Shoebox Fixture



Wall Pack Fixture




High Bay Fixture



Parking Lot




Yard



Street



Stadium



Series	Net Weight	Unit	Package Size	Volume
NGWL-30W12S	0.35 kg/ 0.77 lbs	1 pcs	23.5x12.5x12.5cm/ 9.25"*4.92"*4.92"	0.004m ³
		18 pcs	48.5x40.5x40.5cm/ 19.09"*15.94"*15.94"	0.080m ³
NGWL-60W12S	0.491 kg/ 1.08 lbs	1 pcs	29.5x12.5x13cm/ 11.61"*4.92"*5.12"	0.004m ³
		16 pcs	53x31x53.5cm/ 20.87"*12.20"*21.06"	0.088m ³
NG-WL-80W14S	0.817 kg/ 1.80 lbs	1 pcs	28x13.5x13.5cm/ 11.02"*5.31"*5.31"	0.005m ³
		12 pcs	56.5x43x29.5cm/ 22.24"*16.93"*11.61"	0.072m ³
NG-WL-100W14S	0.885 kg/ 1.95 lbs	1 pcs	30.5x13.5x13.5cm/ 12.01"*5.31"*5.31"	0.005m ³
		12 pcs	56x31.5x43cm/ 22.05"*12.40"*16.93"	0.075m ³
NG-WL-120W14S	0.982 kg/ 2.16 lbs	1 pcs	33.5x13.5x13.5cm/ 13.19"*5.31"*5.31"	0.006m ³
		12 pcs	56x34.5x43cm/ 22.05"*13.58"*16.93"	0.083m ³
NG-WL-160W16S	1.046 kg/ 2.31 lbs	1 pcs	37.5x13.5x13.5cm/ 14.76"*5.31"*5.31"	0.007m ³
		12 pcs	56x38.5x13.5cm/ 22.05"*15.16"*5.31"	0.092m ³
NG-WL-200W16S	1.158 kg/ 2.55 lbs	1 pcs	39.5x13.5x13.5cm/ 15.55"*5.31"*5.31"	0.007m ³
		12 pcs	56x41.5x43cm/ 22.05"*16.34"*16.93"	0.099m ³
NG-WL-250W16S	1.281 kg/ 2.82 lbs	1 pcs	37.5x13.5x13.5cm/ 14.76"*5.31"*5.31"	0.007m ³
		12 pcs	56x38.5x43cm/ 22.05"*15.16"*16.93"	0.093m ³
NG-WL-300W16S	1.41 kg/ 3.11 lbs	1 pcs	39.5x13.5x13.5cm/ 15.55"*5.31"*5.31"	0.007m ³
		12 pcs	56x41.5x43cm/ 22.05"*16.34"*16.93"	0.099m ³
NG-WL-80WH	0.837 kg/ 1.85 lbs	2 pcs	32x28x15cm/ 12.60"*11.02"*5.91"	0.013m ³
		12 pcs	58x45x32cm/ 22.83"*17.72"*12.60"	0.083m ³
NG-WL-100WH	0.992 kg/ 2.19 lbs	2 pcs	32x28x15cm/ 12.60"*11.02"*5.91"	0.013m ³
		12 pcs	58x44x34cm/ 22.83"*17.32"*13.39"	0.086m ³
NG-WL-120WH	1.015 kg/ 2.24 lbs	2 pcs	36x30x15cm/ 14.17"*11.81"*5.91"	0.016m ³
		12 pcs	58x44x36cm/ 22.83"*17.32"*14.17"	0.091m ³
NG-WL-160WH	1.19 kg/ 2.62 lbs	2 pcs	39x30x17cm/ 15.35"*11.81"*6.69"	0.019m ³
		12 pcs	58x45x40cm/ 22.83"*17.72"*15.75"	0.104m ³
NG-WL-200WH NG-WL-250WH	1.281 kg/ 2.82 lbs	1 pcs	37.5x13.5x13.5cm/ 14.76"*5.31"*5.31"	0.007m ³
		12 pcs	56x38.5x43cm/ 22.05"*15.16"*16.93"	0.093m ³